



### 40ft 3-axle skeleton semi trailer with JOST 2 inch King Pin

With more than 39 years of experience in production 40ft 3-axle skeleton semi trailer with JOST 2 inch King Pin, JUPITER® can supply a wide range of Skeleton Semi Trailer. High quality Skeleton Container Trailer can meet many applications, if you need, please get our online timely service about 40FT Skeleton Trailer. In addition to the product list below, you can also customize your own unique Container Chassis according to your specific needs.

### Product Description

This JUPITER® 40ft 3-axle skeleton semi trailer is suitable for carrying ISO 20FT and 40FT containers, which are mostly used in the port, pier and container yards. 40ft 3-axle skeleton semi trailer with JOST 2 inch King Pin is the best choice for the transportation and operation of 20ft and 40ft container van box with high efficiency and economic return, we use famous brand parts on 40ft 3-axle skeleton semitrailer with 8 or 12 locks, such as FUWA or BPW Brands Axle, JOST King Pin. so we recommend the end users or drivers to choose this 40ft 3-axle skeleton semi trailer with Fuwa 13T axle and welcome to inquiry about our 40ft 3-axle skeleton semi trailer.

## JUPITER 40FT 3-AXLE SKELETON SEMI TRAILER Parameter (Specification)

Specification:	
Type:	40FT3 Axles Skeleton Trailer
Model:	JPT9405TJZG
Dimension:	
Length:	12,420mm
Width:	2,480mm
Height:	1,540mm
Wheel Base:	7600+1310+1310mm

<b>Frame &amp; Structure:</b>	
Main beam:	Material Q345B. Fabricated "H" beam height 500mm, Top flange thickness 12mm, Middle web thickness 6mm, Bottom flange thickness 14mm
Side beam:	14# channel steel
Platform:	2.5mm thick diamond plate with supporting channel, 4 lines 40*30 shaped steel
Kingpin:	2'(50#), bolted in type
Twist lock:	8sets twist locks
Welding standard:	All welding are to be done by qualified welder per applicable national standard
Painting:	Shot blast at Standard SA 2.5 prior to application of primer, polyurethane top coat. Total DFT not less than 100um
<b>Running gear:</b>	
Suspension:	mechanicalsuspension,heavy duty leaf spring 8pcs-16mmx90mm, China
Axle:	Factory standard3pcs*13 ton capacity, China
Brake system:	Dual line pneumatic brake, SAE hose and connector,without ABS
Brake chamber:	4 unitsT30/30 spring brakechambers, 2 units T30 brake chambers
Air tank:	40L,1pc, China
Tire:	11R22.5, 12pcs. China
Rim:	8.25*22.5 steel disc wheel, 10 holes ISO, 12pcs. China
Landing gear:	Fuwa 28T two speed telescopic manual landing gear
<b>Electrical System:</b>	
Voltage:	24 Volt
Receptacle:	7 way socket SAE standard, China
Front marker lamp:	White
Side marker	White & Red

lamp:	
Rear lamp:	Red
Turn signal lamp:	Amber
Reflector:	Per customer requirement
Wiring:	Electric cable protected by PVC conduit on main frame
<b>Accessories:</b>	
Mud guard:	Steel mud guard
Spare wheel carriers:	1 pc
Tool box:	1 pc
<p>Note: All the details not mentioned above should comply with Chinese regulations. If any component or structure changed, the price shall be modified accordingly.</p>	